## 2022

## can-am. **OUTLANDER 450/570 T**

## **HIGHLIGHTS**

• Rotax® engine

Rear

- Continuously Variable Transmission (CVT) with engine braking
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok† auto-locking front differential
- Up to 750 kg of towing capacity5.4-gal (20.5 L) fuel capacity
- 25-in. (63.5 cm) Carlisle Trail Wolf tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Multifunction digital gauge
- Steel racks with LinQ<sup>™</sup> quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment RF Digitally Encoded Security System (D.E.S.S.™)



ENGINES	450	570
Туре	28 kW (38 hp), Rotax® 427 cc single cylinder, liquid cooled	36 kW (48 hp), Rotax® V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Visco-Lok† auto-locking front differential	
Power Steering	N/A	
Speed Category	Up to 60 km/h	
SUSPENSIONS		

1 Ower Steering	IN/A	
Speed Category	Up to 60 km/h	
SUSPENSIONS		
Front Suspension	Double A-arm	
	9 in. (22.9 cm) travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI)	
	8.8 in. (22.4 cm) travel	
Rear Shocks	Oil	
TIRES / WHEELS		
Front Tires	Carlisle† Trail Wolf 25 x 8 x 12 in.	
	(63.5 x 20.3 x 30.5 cm)	
Rear Tires	Carlisle† Trail Wolf 25 x 10 x 12 in.	
	(63.5 x 25.4 x 30.5 cm)	
Wheels	12-in. (30.5 cm) steel	
BRAKES		
Front	Dual 214 mm disc brakes with	
	hydraulic twin-piston calipers	

DIMENSIONS / CAPACITIES		
Estimated Dry Weight *	678 lb (308 kg)	
LxWxH	83 x 46 x 49 in. (211 x 116.8 x 124 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	10.5 in. (26.7 cm)	
Seat Height	33.8 in. (85.8 cm)	
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)	
Storage Capacity	Rear: 2.9 gal (10.9 L)	
Towing Capacity	750 Kg trailer with brakes and 335 kg trailer without brakes	
Fuel Capacity	5.4 gal (20.5 L)	

	<u> </u>
FEATURES	
Gauge	4.5-in. digital display:  Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	70 W from dual 35-W front light / brake light
Winch	Prewired for available winch
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
Seat	Standard
Protection	N/A
WARRANTY	
Factory warranty	2-year BRP limited warranty



Single 214 mm disc brake with hydraulic twin-piston caliper

