

can-am

OUTLANDER MAX 450 T

2022

HIGHLIGHTS

- Rotax® engine
- Continuously Variable Transmission (CVT) with engine braking
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok auto-locking front differential
- 5.4-gal (20.5 L) fuel capacity
- Up to 750 kg of towing capacity
- 25 in. (63.5 cm) Carlisle Trail Wolf tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Multifunction digital gauge
- Steel racks with LinQ™ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment
- RF Digitally Encoded Security System (D.E.S.S.™)
- Multiposition passenger handgrips



Viper Red

ENGINE

| | |
|----------------------|--|
| Type | 28 kW (38 hp), Rotax® 427 cc single cylinder, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | CVT, P / R / N / H / L, standard engine braking |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok auto-locking front differential |
| Power Steering | N/A |
| Speed Category | Up to 60 km/h |

SUSPENSIONS

| | |
|------------------|--|
| Front Suspension | Double A-arm 9 in. (22.9 cm) travel |
| Front Shocks | Oil |
| Rear Suspension | Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel |
| Rear Shocks | Oil |

TIRES / WHEELS

| | |
|-------------|--|
| Front Tires | Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) |
| Rear Tires | Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) |
| Wheels | 12 in. (30.5 cm) steel |

BRAKES

| | |
|-------|---|
| Front | Dual 214 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm disc brake with hydraulic twin-piston caliper |

DIMENSIONS / CAPACITIES

| | |
|------------------------|---|
| Estimated Dry Weight * | 715 lb (324 kg) |
| L x W x H | 91 x 46 x 52.5 in (231 x 116.8 x 133 cm) |
| Wheelbase | 59 in. (149.9 cm) |
| Ground Clearance | 10.5 in. (26.7 cm) |
| Seat Height | 33.8 in. (85.8 cm) |
| Rack Capacity | Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg) |
| Storage Capacity | Rear: 2.9 gal (10.9 L) |
| Towing Capacity | 750 kg trailer with brakes and 335 kg trailer without brakes |
| Fuel Capacity | 5.4 gal (20.5 L) |

FEATURES

| | |
|---------------------|---|
| Gauge | 4.5 in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock |
| Instrumentation | Lighter type DC Outlet in console, standard connector in the back (15-A) |
| Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.™) |
| Lighting | 70 W from dual 35-W front light / brake light |
| Winch | Prewired for available winch |
| T-Category features | Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn |
| Seat | Standard |
| Protection | N/A |

WARRANTY

| | |
|------------------|-----------------------------|
| Factory warranty | 2-year BRP limited warranty |
|------------------|-----------------------------|

©2021 Bombardier Recreational Products Inc (BRP). All rights reserved. "™", "®" and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

