## 2022

# can-am. **OUTLANDER MAX DPS 450 T**

## **HIGHLIGHTS**

- Rotax® engine
- Continuously Variable Transmission (CVT) with engine braking
  Tri-Mode Dynamic Power Steering (DPS)
- Anti-Lock Braking System (ABS)
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- 5.4-gal (20.5 L) fuel capacity
- Up to 750 kg of towing capacity
  Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Multifunction digital gauge
- Steel racks with LinQ<sup>™</sup> quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment RF Digitally Encoded Security System (D.E.S.S.™)
- 500-W magneto



| FNG |  |
|-----|--|
|     |  |
|     |  |

| Туре                 | 28 kW (38 hp), Rotax® 427 cc single cylinder,<br>liquid cooled              |
|----------------------|---|
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with<br>Electronic Fuel Injection (EFI) |
| Transmission         | CVT, P / R / N / H / L, standard engine braking                             |
| Drive Train          | Selectable 2WD / 4WD<br>with Brake Traction Control (BTC)                   |
| Power Steering       | Tri-Mode Dynamic Power Steering (DPS)                                       |
| Speed Category       | More than 60 km/h   |

## SUSPENSIONS

| Front Suspension | Double A-arm<br>9 in. (22.9 cm) travel                               |
|------------------|--|
| Front Shocks     | Oil  |
| Rear Suspension  | Torsional Trailing arm Independent (TTI)<br>8.8 in. (22.4 cm) travel |
| Rear Shocks      | Oil  |

## TIRES / WHEELS

| Front Tires | Carlisle† Trail Wolf 25 x 8 x 12 in.<br>(63.5 x 20.3 x 30.5 cm)  |
|-------------|--|
| Rear Tires  | Carlisle† Trail Wolf 25 x 10 x 12 in.<br>(63.5 x 25.4 x 30.5 cm) |
| Wheels      | 12 in. (30.5 cm) cast-aluminum                                   |
|             |  |

### **BRAKES**

| Front | Dual 214 mm disc brakes with hydraulic twin-piston calipers |
|-------|---|
| Rear  | Single 214 mm disc brake with hydraulic twin-piston caliper |
|       |   |

#### **DIMENSIONS / CAPACITIES**

| DIMENSIONO / OAI ASITIES |   |
|--------------------------|---|
| Estimated Dry Weight *   | 715 lb (324 kg)   |
| LxWxH                    | 91 x 46 x 52.5 in (231 x 116.8 x 133 cm)                        |
| Wheelbase                | 59 in. (149.9 cm)   |
| Ground Clearance         | 10.5 in. (26.7 cm)  |
| Seat Height              | 33.8 in. (85.8 cm)  |
| Rack Capacity            | Front: 120 lb (54.4 kg) /<br>Rear: 240 lb (109 kg)              |
| Storage Capacity         | Rear: 2.9 gal (10.9 L)  |
| Towing Capacity          | 750 kg trailer with brakes and<br>335 kg trailer without brakes |
| Fuel Capacity            | 5.4 gal (20.5 L)  |
|                          |   |

#### **FEATURES**

| Gauge               | 4.5-in. digital display:   |
|---------------------|--|
|                     | Speedometer, tachometer, odometer,   |
|                     | trip & hour meters, gear position,   |
|                     | 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock |
|                     | electronic ruer gauge & clock  |
| Instrumentation     | Lighter type DC Outlet in console, standard connector in the back (15-A)   |
| Anti-theft System   | RF Digitally Encoded Security System                                       |
|                     | (D.E.S.S.™)  |
| Lighting            | 70 W from dual 35-W front light / brake light                              |
| Winch               | Prewired for available winch   |
| T-Category features | Towing hitch with trailer plug, directional                                |
|                     | indicators, position lamps, mirrors, horn                                  |
| Seat                | Convertible Rack System (CRS)  |
| Protection          | N/A  |

### WARRANTY

2-year BRP limited warranty Factory warranty



