2022

CON-OM. MAVERICK TRAIL DPS 700 T

HIGHLIGHTS

• Sturdy engine and transmission

Easy Handling and capabilities

· Front and rear suspension designed for trail riding

ADVENTUROUS

Meaningful functionalities and versatilitiesEnhanced comfort with Ergo-Lok cockpit

Build your Maverick Trail that fits your needs

CONFIDENT

• Can-Am design and proven fit & finish

Enhanced protection

More adventure and less maintenance

PLATFORM FEATURES

• 62.8 in. (159.6 cm) wide • 90.6 in. (230.1 cm) wheelbase

• 10 in. (25.4 cm) of ground clearance

• Up to 10.5 in. (26.7 cm) suspension travel

• 7.6 in. (19.3 cm) wide digital display with keypad

• SPORT / ECO[™] modes

· Net (instead of doors)

• RF D.E.S.S. with Start / Stop button

Mudguard and Mudflap

· Rear hitch and tow ball

• 7-pin trailer connexion (12V)

• LED tail lights with halo glow effect

 Horn, flashers and position lamps, left/right mirrors, license plate support, hook on front metal bumper, driver seat

detector, low brake fluid sensor

Over 60 km/h top speed

SPECIFIC TO DSP 700 T PACKAGE Dynamic Power Steering (DPS™)

• 12 in. (30.5 cm) aluminum wheels

• Ergoprint seats with color accents

 Dynamic Brake Control (ABS + HHC + HDC)

• Dynamic Traction Control (BTC + DTC)

|--|

Туре	39 kW (52 hp) / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid cooled, with catalytic converter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary CVT with engine braking and Electronic Drive Belt Protection L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Open front diff. with Brake Traction Control (BTC)
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar / 10.5 in. (26.7 cm) travel
Rear Shocks	Twin tube gas charged shocks
TIRES / WHEELS	
Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast-aluminum



DIUUCEO	
Front	Dual 220 mm disc brakes with hydraulic twin- piston calipers with Dynamic Brake Control (ABS + HHC + HDC)
Rear	Dual 220 mm disc brakes with hydraulic twin- piston calipers with Dynamic Brake Control (ABS + HHC + HDC)

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1,271 lb (576.5 kg)
Chassis / Cage	Profiled cage
	ROPS approved
LxWxH	118 x 62.8 x 69 in.
	(300.5 x 159.6 x 175.3 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	10 in. (25.4 cm)
Cargo Box Capacity	300 lb (136 kg)
Towing Capacity	1,500 lb (682 kg)
Storage Capacity	Total: 5.3 gal (20.2 L)
	Glove Box: 4.1 gal (15.6 L)
	Driver storage: 0.4 gal (1.5 L)
	Center console and Cup holders: 0.8 gal (3.1 L)
Fuel Capacity	10 gal (38 L)

7.6 in. (19.3 cm) wide digital display with

keypad, Speedometer, tachometer, odometer,

FEATURESGauge

	trips and nour meters, ruel, gear position, SPORT / ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (20-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	Two 55 W reflectors and LED tail lights with halo glow effect
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper, Full skid plate Mudguard and Mudflap
Hitch Type	2 in. hitch receiver with rear hitch and tow ball

WARRANTY

Factory warranty	2-year BRP limited warranty



